

SERVICE PRO[®]

Premium Lubricants

SERVICE PRO[®] PREMIUM GLOBAL FULL SYNTHETIC MULTI-VEHICLE ATF

Manufactured with highly refined virgin base oils

DESCRIPTION: SERVICE PRO[®] Premium Global Full Synthetic Multi-Vehicle ATF represents the latest technology in full synthetic automatic transmission fluids. It is specifically formulated for the newest generation of high efficiency transmissions and is also a fuel efficient choice for older models as well.

SERVICE PRO[®] Premium Global Full Synthetic Multi-Vehicle ATF may be used in a wide variety of applications including all General Motors, Ford, Chrysler, Toyota/Lexus, Nissan/Infiniti, and Honda/Acura transmissions; as well as transmissions installed in all* Hyundai, Isuzu, Jaguar, Kia, Land Rover, Mazda, Mercedes, Mitsubishi, Porsche, BMW, MINI, SAAB, Subaru, Suzuki, Volvo and VW/Audi cars and light trucks. Check owner's manual for specific recommendations.

This product is not recommended for Ford Type F, Continuously Variable Transmissions (CVT) or Double Clutch Transmissions (DCT).

**PERFORMANCE
BENEFITS:**

- Improved oxidation and thermal stability
- Full synthetic formula
- Outstanding low temperature performance
- Superior anti-wear protection
- Improved torque transfer

*Currently it is not recommend for VW and Audi transmissions specifying G 055162 A1/A2/A6 or G 060162 A1/A2/A6

Note: This product is not for sale or use in the State of California.

TYPICAL PROPERTIES:	API Gravity	34.8
	Sp. Gr. @ 60 ^o F	0.8468
	Flash, COC, ^o F	400
	Pour Pt., ^o F	-55
	Viscosity, cP @ -40 ^o C	12100
	Viscosity, cSt @ 40 ^o C	32
	cSt @ 100 ^o C	6.3
	Viscosity Index	152
	Color	Red



Updated: 11//11
SPWNGLATF

SERVICE PRO®

Premium Lubricants

SERVICE PRO® PREMIUM GLOBAL FULL SYNTHETIC MULTI-VEHICLE ATF

Manufactured with highly refined virgin base oils

Service Pro Global Full Synthetic Multi-Vehicle Automatic Transmission Fluid is suitable for use in the following applications:

ATF Type A- Suffix A	Hyundai SP-II, SP-III, SP-IV, and SPH-IV	Nissan Matic-D, Matic-J, Matic-K, Matic-S,
Aisin Warner A-1,3309	Idemitsu K17, Jatco 3100 PL085	Opel (all vehicles)
Allison C-3, C-4	Infiniti, Matic-D, Matic-J, Matic-K	Peugeot ZF 4HP20
Alfa Romero (all vehicles)	Isuzu (all vehicles)	Porsche ZF 5HP19FL, ATF 3403-M115, T-IV
American Motors ATF+3, +4	Jaguar M1375.4, ATF 3403 M115	Renault (all vehicles)
ATF 3403 M115	JASO 1-A	Saab 93 165 146, 93 165 147, 3309
Audi ZF, 5HP19FL, 5HP24A, LT71141, G-052-162-A1, G-052-162-A2, G-055-005-A2	Jeep (ATF+3, ATF+4)	Scion (all vehicles)
BMW ZF, 5HP18FL, 5HP24, 5HP30, LA2634, 7045E, LT71141, LA2634, M-1375.4 fluids	JWS 3309	Shell 3403, 3353, LA2634, M-1375.4
Caterpillar Power Shift TO-2	KIA SP-II, SP-III, SP-IV Fluids, Red 1	Subaru ATF, ATF-HP
Chrysler 7176-E, ATF+3, and ATF+4 **	Lexus-Type T, T-II, T-III, T-IV	Suzuki ATF 3317
Daewoo LT71141	MAN 339 F, Type F, V1	Texaco ETL-7045E, ETL-8072B, N402
Esso LT 71141	Mazda M-V, ATF-MIII	Toyota / Lexus Type T,T-II T-III and T-IV, WS
Fiat (all vehicles)	Mercedes Benz ZF 4HP20, MB236.1, MB236.2, MB 236.3(PSF), MB 236.5(C-4), MB236.6, MB236.7, MB 236.8, MB236.9, MB236.10, MB 236.12, NAG-1	Vickers M-2950-S, I-286-S
Ford MERCON®, MERCON® V, MERCON® LV, MERCON® SP, FNR5 (for Mazda), M2C138-CJ, M2C166-H, MC2C924-A*	Mini Cooper T-IV (except CVT)	Voith H55.6335.XX (G607), Turbo, ZF, Ecomat, ZF TE-ML 09/11, ZF TE-ML 03D, 04D, 09, ZF TE- ML 16L, 17C
GM 9986195, Strasbourg, 12378515 (Transynd) DEXRON® II, II-E, III, III-G, III-H and VI *	Mitsubishi Diamond SP II, SP III	Volvo 97340, 1161521, 1161540, T-IV, STD 1273.41
Honda/Acura ATF-Z1, DW-1 (except in CVTs)	Miscellaneous OEMs – M1375.4	VW TL521-62, G-052-162-A1, A2
	MOPAR AS68RC ATF	ZF TE-ML-16L, 17C

*Chrysler ATF +4® is a registered trademark of Chrysler Group LLC./ Dexron® is a registered trademark of General Motors Corp./

Mercon® is a registered trademark of Ford Motor Company

Updated: 01/12
SPWNGLATF

